NOVA SALT W

SUBMERSIBLE PUMPS



TECHNICAL DATA

Operating range:

from 1 to 7.5 m³/h with head up to 6 metres.

Liquid temperature range:

from 0 $^{\circ}$ C to +35 $^{\circ}$ C for domestic use.

Pumped liquid: dirty water, without fibre, including salt water.

Max. immersion depth: 7 metres.

APPLICATIONS

The vertical delivery draining submersible pump has been specifically built for draining applications in salt water installations. It may also be used as a portable pump in emergency situations. The built-in float level switch, in the automatic version, allows fixed installation, ensuring automatic operation.

CONSTRUCTION FEATURES OF THE PUMP


Hydro resistant technopolymer pump body, cover, and suction grid. AISI 316 stainless steel motor, rotor shaft, and bolts and screws. Cable with tin plated conductors.

CONSTRUCTION FEATURES OF THE MOTOR

Submersible type continuous duty asynchronous motor. Thermal overheating protection.

MATERIALS


N.	PARTS		MATERIALS				
1	FILTER BASE		TECHNOPOLYMER				
2	SUCTION STRAINER		TECHNOPOLYMER				
3	OR RING		NBR				
4	IMPELLER		TECHNOPOLYMER				
5	V. RING		NBR				
6	NUT		AISI 316 STAINLESS STEEL DIN 982				
7	WASHER		A2 STAINLESS STEEL				
		CASE	ALUMINIUM				
8	MOTOR	ROTOR SHAFT	AISI 316 STAINLESS STEEL UNI EN 10088-1 X5CRNIM01712-2				
9	BODY		TECHNOPOLYMER				
10	OR RING		NBR				






NOVA SALT W - SALT WATER SUBMERSIBLE PUMPS

Liquid temperature range: from 0 °C to +35 °C for domestic use





The performance curves are based on kinematic viscosity values = $1 \text{ mm}^2/\text{s}$ and density equal to 1000 kg/m^3 . Curve tolerance according to ISO 9906.

MODEL	Q=m³/h	0	1	2	3	4,5	5	6	7	7,5
	Q=I/min	0	16,6	33,3	50	75	83,3	100	116,6	125
NOVA SALT W M-A	H (m)	6	5,4	4,7	3,9	2,8	2,5	1,7	1	0,5

	ELECTRICAL DATA									
MODEL	POWER INPUT	P1 MAX	P2 N0	In						
	50 Hz	kW	kW	HP	A					
NOVA SALT W M-A	1 x 230 V ~	0,28	0,2	0,28	1,3					

	MODEL	A B	D	C	C D	E	Н	H1	DNM GAS	PACKING DIMENSIONS			CABLE	VOLUME	WEIGHT
	MODEL		D							L/A	L/B	Н	UADLE	(m³)	kg
	NOVA SALT W M-A	140	48	107	95	195	270	230	1"%	193	193	330	10 mt.	0,012	3,9

