

LMKAS	External diameter of the bearing	D*	d*	s	h	Number of waves	Constant load [kg/mm]	Maximum load
10	10	9.8	6.2	0.2	1.2	3		
13	13	12	7.2	0.2	1.4	3	13	20
16	16	15.8	10.5	0.3	1.5	3	23.5	35
16 A	16	15.8	10.5	0.15	1.35	3	13	17
18	18	17	12	1.3	1.5	3	12	16
19	19	18.8	11.4	0.3	1.6	3	30	50
19 A	19	18.8	13.2	0.2	1.6	3	6.5	25
22	22	21.8	14	0.3	1.6	3	15	35
22 A	22	21.8	15.8	0.2	1.6	3	4.5	11.5
22 AS	22	21.8	15.8	0.2	2.5	3	3	40
22 H	22	21.8	15.8	0.25	3	3	3	15
22 S	22	21.8	15.8	0.3	2.35	3	4	40
24	24	23.8	17.5	0.3	1.7	3	10	18.5
24 A	24	23.8	17.5	0.2	1.7	3	3.5	12
26	26	25.8	19.3	0.3	1.7	3	8	18
26 A	26	25.8	19.3	0.5	1.7	3	30	46
28	28	27.8	21	0.3	1.7	3	5.5	11
28 A	28	27.8	21	0.5	1.7	3	30	55
28 FG	28	27.8	20	0.3	3	3	5.5	18
30	30	29.7	22.5	0.3	1.8	3	5.5	13
30 A	30	29.7	22.5	0.2	1.7	3	1.7	4
30 B	30	29.7	22.5	0.5	2	3	23.5	57
30 C	30	29.7	22.5	0.4	1.6	3	19.5	26.5
32	32	31	26.5	0.4	2	3	5	21
32 A	32	31.7	26.5	0.4	2	3	4.5	17
32 B	32	31.7	24.5	0.35	2.2	3	5.5	26
32 E	32	31.7	26.5	0.5	2.4	3	10	39
32 FG	32	31.8	23	0.3	3.5	3	5.5	22
32 T	32	31	26.5	0.3	2.7	3	2.5	15
35 A	35	34.5	24.5	0.5	2.5	4	60	120
35 B	35	34.5	28	0.5	3	3	10.5	55
35 C	35	34.9	25	0.3	2	4	17	39
35 E	35	34.5	28	0.4	3	3	6	55
35 FG	35	34.5	28.3	0.4	4	3	4.5	45
35 S	35	34.5	28	0.4	3	3	6	54
37	37	36.6	30.8	0.5	2.5	4	15	50
37 A	37	36.6	30.8	0.3	2.5	4	5.5	15

LMKAS	External diameter of the bearing	D*	d*	s	h	Number of waves	Constant load [kg/mm]	Maximum load
40	40	39.1	33	0.5	3	4	16	65
40 A	40	39.1	33	0.5	4	4	19	68
40 B	40	39.8	33.3	0.3	3	4	4.5	23
40 D	40	39.1	33	0.4	2.7	4	11	35
40 FG	40	39.8	30	0.4	5	3	5	44
42	42	40	30	0.5	3	4	21	69
42 A	42	40	33.1	0.5	3	4		
42 C	42	40	30	0.3	3	4		
42 D	42	41	34.5	0.35	3	4	6	26
47 A	47	45	37	0.5	3	4	15	65
47 B	47	46.5	40	0.5	3	4	14	55
47 C	47	46.9	37	0.5	2	4	24	86
47 E	47	46.5	40	0.4	3	4	7	34
47 F	47	45	37	0.5	3	5	25.5	72
52 A	52	51	42	0.5	3.5	5	21.5	130
52 B	52	51.8	41	0.5	2	4	13	23
52 C	52	51.8	41	0.3	1.9	4		
52 D	52	51	42	0.4	3.5	4	13.5	71.5
52 E	52	51.8	41	0.5	3.5	5	33	95
52 F	52	51.8	41	0.4	2	4	8.5	18.5
52 G	52	51.8	41	0.4	4	4	10	65
52 H	52	51	44	0.4	3.5	4	5.5	26
55	55	54.8	46.9	0.5	2	4	5	33
55 A	55	54.8	46.9	0.5	3.5	4	7	36
58	58	57	48	0.5	3.5	4	16	50
62	62	61	51	0.5	3.5	5	32	95
62 A	62	61	51	0.5	4	4	10	57
62 B	62	61.9	50	0.5	4	4	14	115
62 C	62	61.9	50	1	3.5	4		
62 D	62	61	51	0.4	3.5	4	13	38
62 G	62	61	51	0.6	3.5	5	32	130
62 S	62	62.9	54.2	0.4	3.7	4	6	35
68	68	67.9	55	0.6	4	4	15	67
72	72	71	61	0.5	3.5	5	12.5	57
72 A	72	71	61	0.5	4	4	6	37.5
72 B	72	71.8	58	0.6	4	4	17	70
72 D	72	71	61	0.4	3.5	5	8.5	33

LMKAS	External diameter of the bearing	D*	d*	s	h	Number of waves	Constant load [kg/mm]	Maximum load
72 G	72	71	61	0.8	4	5	52	175
75	75	74.8	66	0.6	4	4	7.5	35
80	80	79	71	0.6	3.5	6	27	88
80 A	80	79	71	1	4	6		
80 B	80	79.8	64	0.7	4	4	26	100
80 C	80	79	71	0.5	3.5	5	7	26
80 F	80	79	71	0.8	4	6	52	175
85	85	84	74	1	4	6		
85 A	85	84	74	0.6	3.5	6	28.5	110
85 B	85	84.8	70	0.8	4	6		
85 C	85	84	74	0.5	3.6	5	7.5	33
90 A	90	89	79	0.6	3.5	6	25	78
90 B	90	89.8	72	0.8	4	4	34	135
90 C	90	89	79	0.5	3.5	6	16	55
100	100	99.8	82	1	4	6		
100 A	100	99	89	0.6	3.5	6	20	66
100 B	100	99.8	82	0.9	4	4	35	110
100 C	100	99	89	0.5	4	6	10	46
110	110	109	90	1	4	4	22.5	125
110 A	110	109	90	1.5	5	6		
110 B	110	109	99	0.6	4.5	7	23.5	117
110 C	110	109	99	0.7	4.5	7	33	170
110 D	110	109	99	0.5	4.5	7	15	65
110 E	110	109	99	1	5	7		
120	120	119	104	0.8	4	6	49	175
125	125	125	109	0.8	4	6	45	150
130	130	129	110	0.8	4	6	45	150
140	140	139	121	0.9	4	6	43	160
150	150	149	126	0.9	4	6	50	150
160	160	159	137	1	4	6	41	165
170	170	169	147	1	4	6	58	175