







NOVAIR 200/600 SUBMERSIBLE AERATOR

FOR DOMESTIC WASTE WATER TREATMENT SYSTEMS
AND POND/FISH FARMING APPLICATIONS







APPLICATIONS

The submerged aerator is designed for liquid waste aeration in small water treatment systems. Other fields of application include pond water oxygenation and fish farming



FUNCTIONING










SBR WASTE WATER TREATMENT SYSTEM OEM COSTUMER








CONSTRUCTION FEATURES

N	DESCRIPTION		MATERIAL
1	PUMP BODY		TECHNOPOLYMER
2	GIRANTE		TECNOPOLIMERO
3	0-ring SEAL		NBR 70
4	MOTOR	CASING	AISI 304
		SHAFT	AISI 416
5	CERAMIC BUSH		AISI 303 + CERAMIC
6	RADIAL SEAL		NBR 70
7	V-RING		NBR 70 + GREASE



Motor: Two-pole asynchronous submergible type motor from 0.18 and 0.4 kW with built-in **thermal protection** and permanently connected capacitor installed in the cable compartment.

Mechanical seals: Triple interposed ring seal with oil pre-chamber.

Operating range: air delivery 2 - 17 m3/h for depths from 20 – 90 cm

Protection level: IP68

Insulating class: F

Liquid temperature range: from 0 °C to 35 °C according to EN 60335-2-41 standard for domestic use


Liquid quality requirements: sewage from septic tank fibre-less and free from solids, and clear water.

Standard voltage: sigle-phase: 220 – 240 V/ 50 Hz

Power cable: H07RNF8-F of 2mt, 5mt e 10 mt and SCHUKO plug available



PERFORMANCES – NOVAIR 200/600







MAXIMUM RELIABILITY:

- Every single aerator is tested with pressurized air to properly assure that no leakages could get into top housing.
- The body is supplied with a supporting basement
- Motor cooling is guaranteed by large contact surfaces between motor casing and the liquid
- SPECIALLY IMPELLER DESIGN: blade profiles avoid damaging to microorganisms present in the water when starting operation.
- COATED RESIN CABLING :against humidity and leaks
- EASY PLUG: cable gland favours the aerator's maintenance operations and its replacement without unplugging power cable from control panel




















LONG PRODUCT DURABILITY:

 The excellent wear resistance of the stainless steel motor shaft, with ceramic bush around the sealing rings, guarantees long product durability.









270 W

Oxyperl

†

Cable-gland system




Novair



Cable **H07RNF8-F**

Performances





NOVAIR 200/600

SUBMERSIBLE AERATOR

FOR DOMESTIC WASTE WATER TREATMENT SYSTEMS
AND POND/FISH FARMING APPLICATIONS

THANKS FOR YOUR ATTENTION

